

EMCORE-Hawkeye™ Series EG-120 Fiber Optic Gyroscopes (FOG)

emcore®

DATASHEET | OCTOBER 2018

NAVIGATION SYSTEMS



Applications

- Platform Stabilization Applications
- Camera Systems in Aircraft
- Unmanned Aerial Vehicles (UAV)
- Gun Stabilization Systems
- Aeronautics and Aviation

Features

- Industry's Best CSWaP with 1/2 the Weight and 1/3 the Power Requirements of Current Generation FOGs
- Most Affordable Closed-Loop FOG Available
- Fully-Integrated Optics and Electronics
- Next-Generation Field Programmable Gate Array (FPGA) Electronics
- Closed-Loop Design for Improved Drift Stability, Higher Linearity, and Greater Flexibility

U.S. Patent No. 7,746,476; 8,773,665; 8,798,405; 8,823,946

Suitable for Demanding Applications

The EMCORE-Hawkeye™ Series EG-120 FOG module is an ultra-compact, state-of-the-art design that is the smallest, most affordable closed-loop FOG available on the market today. At approximately 1/2 the weight with 1/3 the power requirements of current generation FOGs, the EG-120 delivers the industry's best Size, Weight and Power (SWaP) compared to competing products and is 35% smaller than EMCORE's previous generation EMP series FOGs. The EMCORE-Hawkeye™ EG-120 incorporates advanced, next-generation Field Programmable Gate Array (FPGA) electronics that deliver increased performance and reliability combined with low cost.

The EMCORE-Hawkeye™ series features performance specifications that are ideal for medium accuracy platform stabilization applications such as camera systems used in aircraft, Unmanned Aerial Vehicles (UAVs) and gun stabilization systems. A wide variety of other guidance, navigation and aeronautics applications are supported. The EMCORE-Hawkeye™ FOG platform allows greater selection of performance capabilities to meet a broad range of customer requirements including a low-power (LP) version.

Performance Specifications

Parameter	EG-120	EG-120LP (Low-Power)
Gyro Performance		
Fiber Optic Gyro Type	Closed-Loop	Closed-Loop
Input Rate (maximum)	±1500°/sec	±1500°/sec
Bias In-Run Stability (25 °C)	Digital: ≤1.0 deg/hr, 1σ (max)	Analog: ≤10.0 deg/hr, 1σ
Bias vs. Temp (≤ 1 °C/min); no compensation	Digital: ≤20°/hr, 1σ	Analog: ≤50°/hr, 1σ
Scale Factor Non-Linearity (max rate, 25 °C)	≤250 ppm, 1σ	≤500 ppm, 1σ
Scale Factor vs. Temp. (≤ 1 °C/min); with compensation	≤100 ppm, 1σ	≤1000 ppm, 1σ
ARW (Angle Random Walk) (25 °C)	Digital: ≤0.02°/√hr	Analog: ≤0.1°/√hr
Bandwidth (-3 dB)	Digital: 1000 Hz	Analog: 1000 Hz
Electrical/Mechanical		
Initialization Time (valid data)	≤0.3 secs	≤0.3 secs
Data Interface	Asynchronous Digital Output	N/A
Baud Rate	Up to 1 Mbps	N/A
Data Rate	30K samples/sec data rate (16 bit data)	N/A
Dimensions	2.36" Diameter x 0.83" High (60 mm Diameter x 21 mm High)	2.36" Diameter x 0.83" High (60 mm Diameter x 21 mm High)
Weight, Max	1 Axis: Non-Mag. shielded: 0.09 kg (0.13 lbs)	1 Axis: Non-Mag. shielded: 0.09 kg (0.13 lbs)
Power Consumption, Max (typical)	1 Axis: 4.5W	1 Axis: 1.3W (max w/o TEC) < 1.1W (typical)
Input Voltage	+5, +15, -15 VDC	+5, +15, -15 VDC

EMCORE-Hawkeye™ Series EG-120 Fiber Optic Gyroscopes (FOG)



Performance Specifications (continued)

Parameter	EG-120	EG-120LP (Low-Power)
Environmental		
Temperature: Operating	-40 °C to +75 °C (-40 °F to +167 °F)	-40 °C to +85 °C (-40 °F to +185 °F)
Shock: Operating	800 g, 1 msec	800 g, 1 msec
Vibration: Operating	25 g rms, 20-2000 Hz	25 g rms, 20-2000 Hz
Performance Physical		
Number of Axes	1 Axis	1 Axis
Housing	Anodized Aluminum	Anodized Aluminum
MTBF	100,000 hr	100,000 hr

Scale Compared to U.S. Quarter



**MADE IN
USA**

Information contained herein is deemed to be reliable and accurate as of the issue date. EMCORE reserves the right to change the design or specifications at any time without notice. EMCORE is a registered trademark of EMCORE Corporation in the U.S. and other countries.