

# QRS28

Quartz MEMS Dual Axis Rate Sensor

emcore®



DATASHEET | MAY 2022

Transforming Navigation



## Applications

- Platform Stabilization
- Guidance and Control
- Autopilot Control
- Gun and Optical Line of Sight Stabilization
- Missile Seeker Head Stabilization
- Instrumentation
- Fast Slewing Low Noise Scanning Systems

## Key Performance Features

- Extremely Small Size
- Light Weight
- Fast Turn-On Time
- Low Noise
- Excellent Linearity
- Two Axes of Angular Rate
- Low Power Consumption
- High Reliability Long Life

## Ideal for High-Precision Applications

The QRS28 is a small, lightweight, two-axis MEMS rate sensor offering exceptional performance at a very attractive price. The sensor provides a simple DC-DC operation using two of EMCORE's quartz rate sensors.



The instrument is contained within a hermetically sealed, stainless steel cylinder measuring 1.05" [26.7 mm] x 0.71" [18.0 mm] diameter.

## Performance Highlights

Parameter	QRS28-00100-100	QRS28-00200-100	QRS28-00400-100
Standard Range Full Scale	100°/sec	200°/sec	400°/sec
Full-Scale Output (Nominal)	±3.50 V (Analog DC Voltage)		
Scale Factor	0.035 V/°/sec	0.0175 V/°/sec	0.00875 V/°/sec
Scale Factor Accuracy	±2% (factory set)		
Zero Rate Output (Bias)	<33 mV@25°C		
Bandwidth (-90° Phase Shift)	110 Hz ±10 Hz		



# QRS28

Quartz MEMS Dual Axis Rate Sensor


Transforming Navigation

## Performance Specifications

Parameter	QRS28-00100-100	QRS28-00200-100	QRS28-00400-100
<b>Power Requirements</b>			
Input Voltage (Dual Supply)	+ & - 4.75 to 5.35 Vdc		
Input Current	< 50 mA each supply		
<b>Performance</b>			
Standard Range Full Scale	100°/sec	200°/sec	400°/sec
Full-Scale Output (Nominal)	± 3.50 V (Analog DC Voltage)		
Over-Range Capability	> 110% of Full Scale		
Scale Factor	0.035 V/°/sec	0.0175 V/°/sec	0.00875 V/°/sec
Scale Factor Accuracy	± 2% (factory set)		
Zero Rate Output (Bias)	< 33 mV@25°C		
Linearity Error	< 0.05% of Full Range		
Turn On Time	<1.0 sec		
Random Noise (1-101 Hz)	< 0.005°/sec./√Hz.	< 0.005°/sec./√Hz	< 0.007°/sec./√Hz
Bandwidth (-90° Phase Shift)	110 Hz ±10 Hz		
Input Axis Alignment	<31 mrad, uncompensated**		
<b>Environmental</b>			
Operating Temperature	-55°C to +85°C		
Storage Temperature	-55°C to +105°C		
Shock	300 g's, ½ sine, 5 mSec		
G-Sensitivity	<0.02°/sec/g		
Weight	25 grams (0.88 oz)		

\*\* Reduced X-Axis alignment available – consult factory.

## Dimensions/Scale



## For More Information

+1 866.234.4976 | navigation-sales@emcore.com | emcore.com/nav

## EMCORE Corporation

2015 Chestnut Street  
Alhambra, CA 91803 USA

**P** +1 626.293.3700

**F** +1 626.293.3429

emcore®

ISO9001  
CERTIFIED



© 2022 EMCORE Corporation. All rights reserved.

Information contained herein is deemed to be reliable and accurate as of issue date. EMCORE reserves the right to change the design or specifications of our products at any time without notice. EMCORE and Systron Donner Inertial are registered trademarks of EMCORE Corporation in the U.S. and other countries.

MADE IN  
USA

Released 05.05.2022