

# SDG1400

Quartz MEMS Angular Rate Sensor

emcore®



DATASHEET | DECEMBER 2023

A New Era in Navigation



## Ideal for High Performance Commercial & Industrial Applications

The SDG1400 is a single-axis angular rate sensor that provides exceptional performance with EMCORE's proven Quartz MEMS sensing element and fully self-contained electronics.



By applying design techniques found only in more expensive rate sensors, excellent Bias Stability, Temperature Performance, Noise, and Vibration performance levels have been achieved. The availability of the internal temperature sensors enable bias modeling.

## Applications

- Platform Stabilization
- Optical Camera Stabilization
- Antenna Stabilization & Pointing
- High Speed Ride & Tilt Control
- Robotic Control
- Instrumentation


## Performance Highlights

Parameter	SDG1400-200-200
Standard Range Full Scale	$\pm 200^\circ/\text{sec}$ .
Full Scale Output (Nominal)	$\pm 5.0 \text{ Vdc}$
Scale Factor (at 25°C)	$0.025 \pm 0.004 \text{ Vdc}/^\circ/\text{sec}$
Scale Factor Over Temperature (Dev. from 25°C)	$\leq 0.06\%/^\circ\text{C}$
Bias Calibration (at 25°C)	$\leq 1 \text{ deg}/\text{sec}$ .
Bias Variation over Temperature (Dev. from 25°C)	$\leq 1 \text{ deg}/\text{sec}$ .
Bias Stability (In-Run at Constant Temp., Std. Dev.)	$< 6^\circ/\text{hr}$ . typical
Bandwidth (-90°, incl. temp. effect)	$50 \pm 10 \text{ Hz}$

## Key Performance Features

- Exceptional Bias Stability
- Low Gyro Noise
- Improved Vibration Performance
- DC Voltage Input/High-Level Analog DC Voltage Output
- Rugged Construction in a Very Small Form Factor
- High Reliability & Long Life
- RoHS Compliant

## SDG1400 Allen Variance Plot



# SDG1400

Quartz MEMS Angular Rate Sensor


*A New Era in Navigation*

## Performance Specifications

Parameter	SDG1400-200-200
<b>Power Requirements</b>	
Input Voltage	+ and – 10 to 16 Vdc
Input Current	< 15 mA (each supply, typical)
<b>Performance</b>	
Standard Range Full Scale	$\pm 200^\circ/\text{sec.}$
Full Scale Output (Nominal)	$\pm 5.0$ Vdc
Scale Factor (at 25°C)	$0.025 \pm 0.004$ Vdc/ $^\circ/\text{sec}$
Scale Factor Over Temperature (Dev. from 25°C)	$\leq 0.06\%/^\circ\text{C}$
Bias Calibration (at 25°C)	$\leq 1$ deg/sec.
Bias Variation over Temperature (Dev. from 25°C)	$\leq 1$ deg/sec.
Bias Stability (In-Run at Constant Temp., Std. Dev.)	< 6 $^\circ/\text{hr.}$ typical
G Sensitivity	< 36 $^\circ/\text{hr/g}$
Start-Up Time	$\leq 1.0$ sec
Bandwidth (-90 $^\circ$ , incl. temp. effect)	50 $\pm$ 10 Hz
Damping Ratio	0.7 $\pm$ 0.2
Non-Linearity, (% Full Range)	$\leq 0.03\%$
Output Noise (DC to 100 Hz)	$\leq 0.1^\circ/\sqrt{\text{hr}}$ (< 0.0017 $^\circ/\text{sec}/\sqrt{\text{Hz}}$ )
<b>Environments</b>	
Operating Temperature	-55 $^\circ\text{C}$ to +85 $^\circ\text{C}$
Storage Temperature	-55 $^\circ\text{C}$ to +95 $^\circ\text{C}$
Vibration Operating* (20 – 2000 Hz, Flat Profile)	5 $g_{\text{rms}}$
Vibration Rectification*	< 3.6 $^\circ/\text{hr/g}_{\text{rms}}$
Vibration Survival*	20 $g_{\text{rms}}$
Shock Survival	200 g, 2 ms, 1/2 sine pulse
Weight	< 60 grams

\* Please see user's guide for more information regarding vibration tolerance and sensitivity.

## Dimensions/Scale



## SDG1400 PIN ASSIGNMENT

1	-	-	Power Ground	7	-	-	Built-In Test
2	-	-	+Vdc Input	8	-	-	Temp 2 Output
3	-	-	-Vdc Input	9	-	-	No Connection
4	-	-	Temp 1 Output	10	-	-	Leave Open
5	-	-	Signal Return	11	-	-	Case Ground
6	-	-	Rate Output				

EMCORE P/N 965994 Rev G1

## For More Information

+1 866.234.4976 | navigation-sales@emcore.com | emcore.com

## EMCORE Corporation

2015 Chestnut Street  
Alhambra, CA 91803 USA

**P** +1 626.293.3400

**F** +1 626.293.3429

**emcore**<sup>®</sup>

**ISO9001**  
CERTIFIED



© 2023 EMCORE Corporation. All rights reserved.

Information contained herein is deemed to be reliable and accurate as of issue date. EMCORE reserves the right to change the design or specifications of our products at any time without notice. EMCORE and Systron Donner Inertial are registered trademarks of EMCORE Corporation in the U.S. and other countries.

**MADE IN USA**

Released 12.12.2023